





LL7028 LED 8W, 16W

Applications

LED accent light with multiple beam patterns and retractable shrouds, twin heads each 360° rotatable and 180° tiltable, ideally suited for accent lighting. Mounting bracket supports two fixtures, aiming of each independently adjustable. TRIAC dimming standard.

Dimensions



Specifications

Housing	Die-cast aluminum
Gasket	Silicone rubber
Front Cover	Tempered Glass
LED Optic	Polycarbonate Lens
Surface Finish	AkzoNobel powder coating
Driver Type	Constant current, TRIAC dimming standard
LED CRI	80
Input Voltage	120V/AC
Ambient Temperature	-40°C~45°C
Ingress Protection	IP65

Certifications



Options and Accessories

Shroud



No shroud



Angled retractable shroud



Straight retractable shroud

Housing Color



Black RAL9011



White RAL9016



Gray RAL7012



Mineral bronze



Silver RAL9006

Glareshield



Honeycomb Louver

Ordering Guide:

Example: **ET**¹**7028**² - **C16**³ - **4**⁴ - **15**⁵ - **AS**⁶ - **B**⁷ - **H**

1 Series	2 Power Luminaire Output	3 CCT	4 Beam Angle	5 Shroud	6 Housing Color	7 Accessory
ET7028	C8: COB 4W x2 ≤480lm@3K C16: COB 8W x2 ≤960lm@3K	3: 3000K 4: 4000K	15: 15° 25: 25° 30: 30° 4020: H40°xV20°	NS: No shroud AS: Angled retractable shroud SS: Straight retractable shroud	B: Black RAL9011 W: White RAL9016 G: Gray RAL7012 Z: Mineral bronze S: Silver RAL9006	H: Honeycomb Louver M: Marine ambient corrosion resistance