



LL2209 LED 8W

10"

Applications

Compact and inconspicuous steplights with two types of faceplates for illumination of pathways and indoor and outdoor stairs.


Specifications

Housing	Die-cast aluminum
Louver	Die-cast aluminum
Cover Frame	Die-cast aluminum
Gasket	Silicone rubber
Cover Lens	Tempered diffusing glass
Surface Finish	AkzoNobel powder coating
Driver Type	Constant current
LED CRI	80
Input Voltage	120~277V/AC
Ambient Temperature	-40°C~45°C
Beam Angle	90° Diffuse / Asymmetric(Louver)
Ingress Protection	IP65


Certifications



Dimensions



Photometric Data



Ordering Guide:

Example: **ET2209 - S8 - 3 - D - G - DMG**

1 Series	2 Power Luminaire Output	3 CCT	4 Faceplate	5 Faceplate Colour	6 Accessory
ET2209	S8: SMD LED 8W ≤132lm@3K	27: 2700K 3: 3000K 4: 4000K R: Red G: Green B: Blue	D: Diffuse L: Louver	B: Black RAL9011 W: White RAL9016 G: Gray RAL7012 Z: Mineral bronze S: Silver RAL9006	M: Marine ambient corrosion resistance DMG: 0-10V Dimming