

LL2165-B LED 16W


Applications


Bollard in the form of a free standing steplight, directing light downward and minimizing uplight while revealing the texture of the stepped baffle, ideally suited where a steplight is desired but without a mounting surface.

Specifications


Panel Housing	Extruded aluminum			
Baffle Faceplate	Die-cast aluminum			
Gasket	Silicone rubber			
Concealed Lens	Tempered Glass			
Surface Finish	AkzoNobel powder coating			
Driver Type	Constant current			
LED CRI	80			
Input Voltage	120~277V/AC			
Ambient Temperature	-40°C~45°C			
Light Aperture	Asymmetric			
Ingress Protection	IP65			
Certifications	e De la compania del compania del compania de la compania del compania del compania de la compania del comp			

Dimensions





Photometric Data



Ordering Guide:

Example: $\frac{1}{\text{ET2165-B}} - \frac{2}{\text{C16}} - \frac{3}{3} - \frac{4}{\text{G}} - \frac{5}{\text{DMG}}$

1	2	3	4	5
Series	Power Luminaire Output	ССТ	Faceplate Colour	Accessory
ET2165-B	C16 :LED 16W ≤1384Im@3K	27: 2700K 3: 3000K 4: 4000K 5: 5000K	B: Black RAL9011 W: White RAL9016 G: Gray RAL7012 Z: Mineral bronze S: Silver RAL9006	M: Marine ambient corrosion resistance DMG: 0-10V Dimming