

GALAXY



MAIN FEATURES

- GR100 max 25W, GR125 max 35W, GR150 max 50W;
- High lumen efficiency of 100lm/W;
- Tunable white allow more flexible light adjustment to match the mood;
- Low glare UGR<16 for visual comfort;
- Magnetic reflector design enable tool-free replacement without trouble in positioning;
- IP65 suitable for semi outdoor and wet areas;
- Spring clip to be flexible with ceiling thickness from 1-20mm.

Input Wattage 20W-25W (GR100), 30W-35W (GR125), 40W-50W (GR150)	Delivered Lumens (whole fixture efficiency) 1861-2218lm (20W-25W), 3045-3432lm (30W-35W), 3629-4770lm (40W-50W)
Input Voltage 220-240V / 120V / 277V input, 50-60Hz	Light Color Static White: 2700K, 3000K, 4000K, 5000K Tunable White: 2700K-5000K Full Spectrum: RGBCW
Power Factor Greater than 0.9	Color Quality CRI 90+, SDCM≤3
Dimming Control On-off, 0/1-10V, DALI, TRIAC, CCT Switch, CASAMBI, DMX512	Beam Optics  24°, 38° Spot  50° Flood
Ambient Operating Temperature -20°C to 40°C	Optical Accessories None
Ceiling Thickness  1mm-20mm Spring clip  1mm-30mm Mounting rod	Secondary Reflector  Matt black  Matt white  Matt silver  Gold
Warranty 5 year limited warranty	Lumen Maintenance 50000h@80%(L80)

- Approximate lumen output based on 3000K CRI90 performance.
 Pls send email to sales@encore-tech.com to get product specification and photometric test report.

- GR100 **IC-Rated:** 10W MAX
- GR125 **IC-Rated:** 15W MAX
- GR150 **IC-Rated:** 20W MAX