

GALAXY Cylinder

4"



5"



6"



MAIN FEATURES

- Low glare UGR<16 for visual comfort.
- Tunable white 2700-5000K.
- Wide range of dimming methods.
- Family design in 3 sizes.
- Multiple mounting options: pendant, surface, wall.
- High quality finish in versatile colors.
- IP65 for wet location.

Input Wattage 20W-25W (4"), 30W-35W (5"), 40W-45W (6")	Delivered Lumens 1668lm-2056lm(20W-25W), 2286lm-2718lm(30W-35W), 3219lm-3623lm(40W-45W),
Input Voltage 220-240V / 120V / 277V input, 50-60Hz	Light Color Static White: 2700K, 3000K, 4000K, 5000K Tunable White: 2700K-5000K CCT Selectable : 2700K-4000K
Dimming Control On-off, 0/1-10V, DALI, TRIAC, CCT Switch, CASAMBI	Color Quality CRI 90+, SDCM≤3
Mounting Options  Surface  Pendant  Wall	Beam Optics  24°, 38° Spot  50° Flood
Size  Φ95.5mm L:155mm  Φ123mm L:165mm  Φ146mm L:180mm	Lighting Types  Downlight
Finishes  White  Black  Silver  Bronze  Custom Color	Optical Accessories None
IP Rating Wet Location / IP65 Available	Secondary Reflector  Black  Bright silver  Matt silver  Gold
Warranty 5 year limited warranty	Lumen Maintenance 50000h@80%(L80)