

DELLA-Wall Washer



DM50-DF55RF01






DM60-DF65RF01



MAIN FEATURES

- Flush with ceiling with no dark area.
- Superb uniform illumination of wall.
- Deeply concealed optics for low glare UGR<2 and visual comfort.
- Interchangeable different trim and secondary reflector colors.
- 360° rotatable secondary reflector.

Input Wattage 8W-10W (DM50), 10W-15W (DM60)	Delivered Lumens (whole fixture efficiency) 276-370lm (8W-10W), 518-677lm (10W-15W)
Input Voltage 120-277V AC, 50-60Hz	Light Color Static White: 2700K, 3000K, 3500K, 4000K Tunable White: 2700K-6500K Dim-to Warm: 1800K-3000K (DM60) Full Spectrum: RGBCW (DM60)
Power Factor Greater than 0.9	Color Quality CRI 90+, SDCM≤2
Dimming Control On-off, 0/1-10V, DALI, TRIAC, DMX512	Beam Optics  Wall Washing
Ambient Operating Temperature -20°C to 40°C	Optical Accessories None
Ceiling Thickness  2mm-25mm	Suggested Spacing And Wall Distance 
Warranty 5 year limited warranty	Lumen Maintenance 50000h@80%(L80)

- Approximate lumen output based on 3000K CRI90 performance.
- Pls send email to sales@encore-tech.com to get product specification and photometric test report.
- DM50 **IC-Rated**: 6W MAX
- DM60 **IC-Rated**: 8W MAX