

AVA-Hotel



AM504-AF11RA01














AM506-AF11RA01



MAIN FEATURES

- Elegant & compact in its style, versatile in its using.
- Precise light control, 10°, 15°, 24°, 36°, 50° beam lens options.
- Light efficiency is up to 80 lm/W.
- Interchangeable different color secondary reflectors for decorative function.
- Anti-glare accessories provide maximum visual comfort.
- Precision engineering adjustment mechanism from 0° to 30°,
- Every 5° has a fixed limit to achieve accurate tilt Angle.

Input Wattage 5W-8W (AM504), 10W-15W (AM506)	Delivered Lumens (whole fixture efficiency) 357-511lm (5W-8W), 692-923lm (10W-15W)
Input Voltage 220-240V input, 50-60Hz	Light Color Static White: 2700K, 3000K, 3500K, 4000K Dim-to Warm: 1800K-3000K Full Spectrum: RGBCW
Power Factor Greater than 0.9	Color Quality CRI 90+, SDCM≤3
Dimming Control On-off, 0/1-10V, DALI, TRIAC, CASAMBI, DMX512	Beam Optics <div><div> 10° Ultra Narrow Spot</div><div> 15° Narrow Spot</div><div> 24°, 36° Spot</div><div> 50° Flood</div></div>
Ambient Operating Temperature -20°C to 40°C	Optical Accessories <div> Honeycomb</div> <div> Soft Lens</div>
Ceiling Thickness  Spring Strip 10mm-20mm	Secondary Reflector <div> Matt black</div> <div> Matt white</div> <div> Matt silver</div> <div> Gold</div>
Warranty 5 year limited warranty	Lumen Maintenance 50000h@80%(L80)

- Approximate lumen output based on 3000K CRI90 performance.
Pls send email to sales@encore-tech.com to get product specification and photometric test report.